

THOMSON


DELPHION

RESEARCH

PRODUCTS

INSIDE DELPHION

The Delphion Integrated View

Get Now: ☒ PDF | [More choices...](#)Tools: Add to Work File: [Create new Work File](#) View: [INPADOC](#) | Jump to: [Top](#)  Go to: [Derwent](#) [Email this to a](#)

🔍 Title: **JP59131638A2: OPEN-CELL FOAMED MATERIAL OF CROSSLINKED POLYOLEFIN HAVING HYDROPHILIC PROPERTY AND ITS PREPARATIO**

🔍 Derwent Title: Crosslinked polyolefin open-cell foam - prepd. from polyolefin, foaming agent and crosslinking agent [\[Derwent Record\]](#)

🔍 Country: JP Japan

🔍 Kind: A

🔍 Inventor: YOSHIDA IWAO;
KAWASHIMA YASUO;
KASATSUGU TAKEO;

🔍 Assignee: SANWA KAKO KK
[News, Profiles, Stocks and More about this company](#)

🔍 Published / Filed: 1984-07-28 / 1983-01-18

🔍 Application JP1983000006899

Number:

🔍 IPC Code: C08J 9/06; C08J 9/22;

🔍 Priority Number: 1983-01-18 [JP1983000836899](#)

🔍 Abstract: PURPOSE: To obtain a foamed material having excellent hydrophilic property, water retainability and weather resistance, and the feeling of the human skin, by kneading a polyolefin with a foaming agent and a crosslinking agent, heating the kneaded product under normal pressure to obtain a foamed material, interconnecting the cells of the material by mechanical deformation, and impregnating a water-insolubilized polyvinyl alcohol to the foam.

CONSTITUTION: A foamable and crosslinkable kneaded composition composed of a polyolefin, a foaming agent and a crosslinking agent and free of gel fraction, is heated under normal pressure to effect the simultaneous decomposition of the foaming agent and the crosslinking agent to obtain a foamed material, which is subjected to the mechanical deformation to interconnect the cells with each other. An open-cell foamed material having uniform and fine cell structure and elasticity, an expansion ratio of 15W70 and an open-cell ratio of 80% can be manufactured by this process. A water-insolubilized polyvinyl alcohol is impregnated in the pore. The polyvinyl alcohol has a polymerization degree of about 500W2,000, and the amount is 0.001W0.02g per 1cm³ of the foamed material.

COPYRIGHT: (C)1984,JPO&Japio

🔍 Family: None

🔍 Other Abstract: None

